

MARCH, 1989

PLAT NO. 2 COBBLESTONE, P.U.D.

LYING IN SECTIONS 1 & 12, TOWNSHIP 38 SOUTH, RANGE 39 EAST
MARTIN COUNTY, FLORIDA

I, MARSHA STILLER, CLERK OF THE CIRCUIT COURT OF MARTIN COUNTY, FLORIDA, HEREBY CERTIFY THAT THIS PLAT WAS FILED FOR RECORD IN PLAT BOOK 12, PAGE 23, MARTIN COUNTY, FLORIDA, PUBLIC RECORDS, THIS _____ DAY OF _____, 19____.

MARSHA STILLER,
CLERK CIRCUIT COURT
MARTIN COUNTY, FLORIDA.

BY: _____
DEPUTY CLERK

FILE NO. _____

(CIRCUIT COURT SEAL)

DATA

○	DELTA/BEARING	RADIUS	LEN./DIST.	TANGENT
1	34° 24' 27"	244.38	146.76	75.67
2	09° 49' 05"	1283.97	220.02	110.28
3	79° 24' 50"	25.00	34.85	20.76
4	33° 04' 15"	366.83	211.73	108.91
5	42° 50' 00"	25.00	18.69	9.81
6	265° 40' 00"	50.00	231.84	53.93
7	42° 50' 00"	25.00	18.69	9.81
8	33° 04' 15"	306.83	177.10	91.09
9	79° 24' 51"	25.00	34.85	20.76
10	23° 49' 18"	274.38	114.08	57.88
11	85° 05' 29"	25.00	37.13	22.94
12	11° 32' 17"	910.64	183.38	92.00
13	45° 14' 00"	99.78	78.78	41.57
14	59° 53' 49"	25.00	26.13	14.40
15	263° 02' 49"	50.00	229.55	56.47
16	34° 11' 40"	25.00	14.92	7.69
17	56° 16' 40"	159.78	156.95	85.46
18	11° 32' 17"	970.64	195.46	98.06
19	90° 50' 19"	25.00	39.64	25.37
20	05° 24' 28"	1525.76	144.01	72.06
21	09° 49' 05"	1343.97	230.30	115.43
22	N 89° 55' 36" W		66.01	
23	01° 22' 33"	4742.82	113.89	56.95
24	00° 31' 32"	4742.82	43.50	21.75
25	01° 21' 26"	4742.82	112.34	56.18
26	01° 21' 20"	4742.82	112.21	56.11
27	00° 52' 21"	4742.82	72.22	36.11
28	05° 25' 08"	223.85	21.17	10.59
29	22° 05' 51"	223.85	86.33	43.71
30	21° 27' 52"	223.85	83.86	42.43

DATA

○	DELTA/BEARING	RADIUS	LEN./DIST.	TANGENT
31	04° 11' 09"	223.85	16.35	8.18
32	06° 28' 03"	862.16	74.74	37.41
33	08 17' 01"	862.16	95.73	47.95
34	04° 04' 03"	862.16	47.01	23.51
35	08° 03' 47"	862.16	93.18	46.67
36	0° 51' 55"	862.16	10.00	5.00
37	02° 20' 38"	1725.76	70.60	35.30
38	18° 57' 08"	125.00	41.35	20.86
39	23° 04' 26"	125.00	50.34	25.52
40	20° 44' 22"	125.00	45.25	22.87
41	40° 59' 37"	125.00	89.43	46.73
42	12° 25' 41"	125.00	27.11	13.61
43	18° 14' 50"	250.00	79.62	40.15
44	14° 14' 45"	250.00	62.16	31.24
45	08° 24' 02"	359.78	52.75	26.42
46	07° 57' 58"	359.78	50.02	25.05
47	03° 51' 42"	1170.64	78.90	39.46
48	01° 46' 15"	1170.64	36.18	18.09
49	0° 13' 22"	1543.97	6.00	3.00
50	04° 31' 03"	1543.97	121.73	60.90
51	04° 30' 36"	1543.97	121.53	60.80
52	0° 34' 04"	1543.97	15.30	7.65
53	04° 25' 47"	1225.00	94.71	47.38
54	05° 08' 48"	1225.00	110.04	55.06
55	02° 15' 43"	1265.76	49.97	24.99
56	04° 48' 38"	1265.76	106.27	53.17
57	04° 48' 37"	1265.76	106.27	53.16
58	04° 48' 38"	1265.76	106.27	53.17
59	03° 46' 16"	1265.76	83.31	41.67
60	S 19° 12' 05" W		20.19	

DATA

○	DELTA/BEARING	RADIUS	LEN./DIST.	TANGENT
61	02° 00' 01"	1122.16	39.18	19.59
62	S 57° 21' 16" E		41.00	
63	S 60° 38' 26" E		42.61	
64	S 60° 38' 26" E		50.25	
65	06° 20' 04"	1122.16	124.06	62.09
66	0° 15' 19"	1122.16	5.00	2.50
67	04° 25' 24"	1425.00	110.01	55.03
68	04° 25' 17"	1425.00	109.96	55.01
69	0° 09' 07"	1425.00	3.78	1.89
70	05° 01' 19"	1343.97	117.80	58.94
71	04° 47' 46"	1343.97	112.50	56.28
72	N 85° 33' 39" W		9.27	
73	N 85° 33' 39" W		23.37	
74	23° 18' 10"	214.38	87.19	44.21
75	06° 41' 44"	306.83	35.86	17.95
76	03° 44' 07"	306.83	20.00	10.01
77	33° 35' 28"	50.00	29.31	15.09
78	99° 14' 32"	50.00	86.61	58.79
79	101° 41' 22"	50.00	88.74	61.40
80	31° 08' 38"	50.00	27.18	13.93
81	02° 23' 45"	366.83	15.34	7.67
82	11° 41' 22"	366.83	74.84	37.55
83	S 56° 51' 20" E		4.74	
84	21° 22' 41"	274.38	102.38	51.79
85	N 87° 28' 22" W		18.31	
86	02° 40' 46"	1343.97	60.04	31.43
87	02° 13' 41"	1343.97	49.93	26.13
88	02° 19' 48"	1485.00	80.39	30.20
89	04° 14' 45"	1485.00	110.04	55.05
90	0° 38' 27"	4482.82	50.14	25.07

DATA

○	DELTA/BEARING	RADIUS	LEN./DIST.	TANGENT
91	01° 29' 38"	4482.82	116.88	58.44
92	01° 28' 11"	4482.82	114.99	57.50
93	01° 02' 30"	4482.82	81.50	40.75
94	03° 03' 32"	483.85	25.83	12.92
95	10° 51' 41"	483.85	91.72	46.00
96	11° 21' 45"	483.85	95.95	48.13
97	11° 15' 27"	483.85	95.07	47.69
98	05° 28' 54"	483.85	46.29	23.16
99	11° 08' 40"	483.85	94.11	47.20
100	0° 15' 19"	922.16	4.11	2.05
101	06° 20' 04"	922.16	101.95	51.03
102	06° 23' 09"	922.16	102.78	51.44
103	06° 23' 08"	922.16	102.77	51.44
104	06° 23' 08"	922.16	102.77	51.44
105	02° 00' 01"	922.16	32.19	16.10
106	N 19° 12' 05" E		20.19	
107	03° 46' 16"	1465.76	96.47	48.25
108	02° 15' 43"	1465.76	57.87	28.94
109	S 01° 15' 48" E		30.86	
110	01° 46' 15"	970.64	30.00	15.00
111	05° 54' 20"	970.64	100.05	50.07
112	03° 51' 42"	970.64	65.42	32.72
113	12° 33' 37"	159.78	35.03	17.58
114	22° 02' 13"	159.78	61.46	31.11
115	20° 36' 17"	159.78	57.46	29.04
116	01° 04' 33"	159.78	3.00	1.50
117	76° 41' 17"	50.00	86.92	39.55
118	64° 23' 43"	50.00	56.20	31.48
119	73° 44' 23"	50.00	64.35	37.50
120	48° 13' 26"	50.00	42.08	22.38

DATA

○	DELTA/BEARING	RADIUS	LEN./DIST.	TANGENT
121	45° 14' 00"	99.78	78.78	41.57
122	02° 19' 41"	910.64	37.00	18.50
123	23° 04' 26"	25.00	10.07	5.10
124	82° 01' 03"	25.00	27.06	15.03
125	04° 19' 10"	1525.76	115.02	57.54
126	01° 27' 43"	862.16	22.00	11.00
127	03° 19' 24"	862.16	50.01	25.01
128	06° 15' 37"	862.16	94.20	47.15
129	04° 43' 42"	423.85	34.98	17.50
130	07° 51' 41"	423.85	58.15	29.12
131	00° 52' 04"	4542.82	68.80	34.40
132	01° 21' 37"	4542.82	107.85	53.93
133	01° 21' 37"	4542.82	107.85	53.93
134	00° 32' 55"	4542.82	43.50	21.75
135	01° 20' 58"	4542.82	108.99	53.50